

HD IG

SECTION 1	PRODUCT AND COMPANY IDENTIFICATION
------------------	---

Product Name:	HD IG
Version:	1
Identifier 1:	Vinyl Single Sided Laminate
Identifier 2:	
Chemical Family:	Plastic Laminate, Plastic Sheet
Product Use:	Secondary Containment.
 Company Information:	 Plastatech [®] Engineering Ltd. 725 Morley Dr. Saginaw, MI 48601 Phone: (800) 892-9358 Internet Address: www.plastatech.com
 Emergency Phone (24 hours):	 INFOTRAC 1-800-535-5053 (US & Canada) 1-352-323-3500 (International)

SECTION 2	HAZARD(S) IDENTIFICATION
------------------	---------------------------------

Hazard Classification:	As defined in the OSHA Hazard Communication Standard, 29 CFR 1910.1200, this product is considered an article and does not require an SDS. In addition, articles are not included in the scope of the Globally Harmonization System (GHS). As such, the GHS labeling elements are not included on this SDS. All components listed for this product are bound within the product. When handled as intended and under normal conditions of use, there is no evidence that any of the ingredients are released in amounts that pose a significant health risk. Although these products are not subject to the OSHA Standard or GHS labeling elements, Plastatech [®] would like to disclose as much health and safety information as possible to ensure that this product is handled and used properly. This SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and be made available for employees and other users of this product. In addition, the recommendations for handling and use of these products should be included in worker training programs.
Pictogram(s):	N/A
Signal Word:	N/A
Hazard Statements:	N/A
Precautionary Statements:	N/A

SECTION 3	COMPOSITION/INFORMATION ON INGREDIENTS
------------------	---

Hazardous Ingredients

Chemical Name	CAS Number	Concentration (%)
Ethene, Chloro-, Homopolymer	9002-86-2	Trade Secret
Carbon Black	1333-86-4	Trade Secret
Adipic Acid Polyester	N/A	Trade Secret
Calcium Carbonate	471-34-1	Trade Secret

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

SECTION 4	FIRST-AID MEASURES
------------------	---------------------------

Inhalation: If affected:
 Move to fresh air.
 Aid in breathing, if necessary.
 Get immediate medical attention.

Skin Contact: Wash off with soap and plenty of water.
 If irritation develops, get medical attention.

Eye Contact: Immediately flush eye(s) with plenty of water.
 Remove contact lenses, if present, and easy to do so.
 Keep eye(s) wide open while rinsing.
 If irritation develops, consult a physician.

Ingestion: Unlikely.

Most Important Symptoms and Effects, Both Acute and Delayed: Possible irritant effects.

Protection of First-Aiders: Move out of dangerous area.
 Consult a physician.
 Show this Safety Data Sheet to the doctor in attendance.

Notes to Physician: Treat symptomatically.

SECTION 5	FIRE-FIGHTING MEASURES
------------------	-------------------------------

LEL and UEL: N/A

Flash Point: N/A

Suitable Extinguishing Media: Use dry chemical, foam, water, or Carbon Dioxide to extinguish fire.

Unsuitable Extinguishing Media: N/A

Specific Precautionary Methods: If used at high temperatures, Hydrogen Chloride gas may be formed.

Special Protective Equipment for Firefighters: In the event of a fire, wear NIOSH approved, positive pressure, self-contained breathing apparatus (SCBA) and full protective clothing.

Decomposition Products: Carbon Monoxide, Carbon Dioxide, and Hydrogen Chloride gases.

SECTION 6	ACCIDENTAL RELEASE MEASURES
------------------	------------------------------------

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1940.120).

SECTION 7	HANDLING AND STORAGE
------------------	-----------------------------

Handling Precautions: Avoid exceeding the given occupational exposure limits (see Section 8).
 For personal protection, see Section 8.
 Smoking, eating, and drinking should be prohibited in the application area.
 Follow standard hygiene measures when handling chemical products.

Storage Requirements: Observe label precautions.
 Store in accordance with local regulations.

SECTION 8	EXPOSURE CONTROLS/PERSONAL PROTECTION
------------------	--

Exposure Limits

Component	CAS Number	Basis **	Value	Exposure Limit(s)* / Form of Exposure
Ethene, Chloro-, Homopolymer	9002-86-2	N/A	N/A	N/A
Carbon Black	1333-86-4	OSHA	TWA	3.5 mg/m ³
		ACGIH	TLV	3 mg/m ³ (Inhalation)
Adipic Acid Polyester	N/A	N/A	N/A	N/A
Calcium Carbonate	471-34-1	OSHA	TWA	15 mg/m ³ (50 mppcf)

*The above mentioned values are in accordance with the legislation in effect at the date of the release of this Safety Data Sheet.

****Basis**

- ACGIH. Threshold Limit Values (TLV)
- OSHA P0. Table Z-1, Limit for Air Contaminant (1989 Vacated Values)
- OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant
- OSHA P2. Permissible Exposure Limits (PEL), Table Z-2
- OSHA Z3. Table Z-3, Mineral Dust

Engineering Measures: Use product in a well ventilated area. Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Personal Protective Equipment:

Respiratory Protection

Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand Protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye Protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin and Body Protection

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific workplace.

Hygiene Measures

Avoid contact with skin, eyes, and clothing.

Wash hands before breaks and immediately after handling the product.

Remove contaminated clothing and protective equipment before entering eating areas.

Wash thoroughly after handling.

SECTION 9**PHYSICAL AND CHEMICAL PROPERTIES**

Appearance:	Vinyl Laminate
Physical State:	Solid
Specific Gravity:	1.2 – 1.4
Boiling Point:	> 350°F (> 177°C)
Odor:	Slight Vinyl Odor
Solubility:	Insoluble
Freezing/Melting Point:	N/A
Vapor Pressure:	N/A
Vapor Density:	N/A

SECTION 10**STABILITY AND REACTIVITY**

Hazardous Polymerization:	Will not occur.
Chemical Stability:	The product is chemically stable.
Hazardous Decomposition Products:	Hydrogen Chloride gas, Carbon Monoxide, and Carbon Dioxide.
Conditions to Avoid:	N/A
Materials to Avoid:	Strong oxidizing agents.

SECTION 11**TOXICOLOGICAL INFORMATION****Toxicity**

Hazardous Ingredient Name	Acute or Chronic?	Oral LD ₅₀	Dermal LD ₅₀	Dermal LC ₅₀
Carbon Black	Chronic*	> 15,400 mg/kg (rat)	> 3 g/kg (rabbit)	NE**
Titanium Dioxide				
Ethene, Chloro-, Homopolymer	No	NE**	NE**	NE**
Calcium Carbonate	Acute	NE**	NE**	NE**

**NE = No Evidence

Irritation: Possible skin irritation.
Possible eye irritation.

Sensitization: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

SECTION 12 **ECOLOGICAL INFORMATION**

Environmental Data

Components	Species	Test Results
Carbon Black	Brachydanio Rerio	LC50; Dose: > 1,000 mg/L; Exposure time: 96 h (OECD Guideline 203)
	Daphnia Magna	EC50; Dose: > 5,600 mg/L; Exposure time: 24 h (OECD Guideline 202)
	Scenedesmus Subspicatus	EC50; Dose: > 10,000 mg/L; Exposure time: 72 h (OECD Guideline 201)
	Activated Sludge	EC0; Dose: ≥400 mg/L; Exposure time: 3 h
	Activated Sludge	EC10; Dose: ca. 800 mg/L; Exposure time: 3 h

Other Information: Dispose of this material and its container in accordance with federal, state and local regulations.

SECTION 13 **DISPOSAL CONSIDERATIONS**

Disposal Methods: **Waste from Residues**
 Disposal of this product, solutions, and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any federal, state and local authority requirements.

SECTION 14 **TRANSPORT INFORMATION**

DOT: Not Regulated

Emergency Response Guide (ERG): Not Applicable.

SECTION 15 **REGULATORY INFORMATION**

TSCA List: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

CERCLA Reportable Quantity: This material does not contain any components with a CERCLA RQ.

SARA 304 Reportable Quantity: This material does not contain any components with a section 304 EHS RQ.

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act: This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

Ozone-Depletion Potential: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

California Prop 65:

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause [cancer](#). For more information, go to www.P65Warnings.ca.gov.

SECTION 16

OTHER INFORMATION

Previous Editions:

First Edition: 05/14/2014

Further Information:

This SDS was prepared in accordance with OSHA regulatory standards for Toxic and Hazardous Substances: 29 CFR 1910.1200

Disclaimer:

To the best of our knowledge, the information contained herein is accurate. However Plastatech® Engineering, Ltd. does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be handled with care. Although Plastatech® Engineering, Ltd. has described herein all of the hazards to which we are currently aware; we cannot guarantee that these are the only hazards which exist.